



STONE AND MASONRY ANCHORS

Made to Order

Stone installation must be designed in accordance with acceptable engineering practices and the recommendations of the stone fabricator. Stainless Steel is recommended for stone anchors.

STRAP ANCHORS: Typical dimensions are 3/4" to 2" wide x 16 gage to 3/8" thick x length required.

CORRUGATED ANCHORS: Maximum steel thickness is 3/16", 1/8" for stainless steel.


















































HOLES: Specify center spacing from designated end. Holes are typically 1/16" larger than the diameter of the dowel of fastener used.

TWIST: Twist is 1 3/4" long. Specify the length from the end of the anchor to the start of the twist. Twist is not available on steel larger than 1/4" x 1", 3/16" x 1 1/2", or Stainless Steel larger than 3/16" x 1" or 1/8" x 1 1/2".

SPLIT BENDS: Recommend minimum of 1 1/4" width and minimum 1/2" i.d. split-bend length.

ANCHOR RODS: Continuous or partially threaded rods are available with UNC (course) threads from 6/32" to 2" diameter, and in lengths up to 144".

Stone Anchor Engineering Services are available in certain states through Heckmann for a fee. Call for details.

 140	 141	 143	 144	 145	 147	 148
 150	 151	 152	 152-A	 152-S	 153	 154
 154-A	 155	 157-A	 159	 159-S	 160	 161
 162	 163	 164	 165	 166	 166-A	 166-B
 166-C	 166-D	 167	 167-A	 167-B	 167-D	 170
 174	 177	 177-B	 179	 180	 181	 182
 183	 274	 275-U	 275-Z	 276	 285	 287

MASONRY