



4225 W. Ogden Ave. • Chicago, IL 60623 • Phone: (773) 522-1900

## L&M CURE

### Curing Compound

L & M CURE is a VOC-compliant ready-to-use, non-residual concrete curing agent that penetrates surfaces to cure the concrete within. It is a water-based, clear, sprayable liquid that offers residual free performance. L & M CURE is odor-free and is ideal for use in enclosed vented areas where odor-free products are essential, such as retrofit construction, tunnels or chimneys. L & M CURE can be easily applied to both vertical and horizontal surfaces.

L & M CURE is a water-soluble cure that deeply penetrates concrete surfaces. L & M CURE leaves a residual free surface to which concrete, terrazzo, tiles, paints, epoxies or other toppings will satisfactorily bond.

*Basic Use:* L & M CURE is recommended for areas where non-residual performance is critical and later toppings and sealers are desirable and scheduled.

#### COVERAGE AND PACKAGING

L & M CURE is available in 5 gal. and 55 gal. containers.

#### Coverage Rate

200-300 sq. ft. per gallon  
Roller or Spray applied

## DRESS & SEAL WB & WB 30

### Water-Based, Acrylic Cure, Sealer and Dustproof

DRESS & SEAL WB formulations are water-based, low VOC, acrylic copolymer solutions that cure, seal and dust-proof concrete with minimal yellowing. The tough film locks in moisture, curing the concrete for maximum hardness. These clear, fast drying, sprayable liquids are equally effective on interior as well as exterior surfaces.

DRESS & SEAL WB formulations have a very low odor and dry to form a clear, glossy, protective film that is highly resistant to blushing. They adhere well to concrete surfaces and have excellent barrier properties, particularly to jobsite contaminants, dirt, and a variety of mild chemicals.

*Basic Use:* DRESS & SEAL WB and WB 30 are recommended for use in applications where sealing and dustproof performances are demanded such as: warehouses, office buildings, driveways, sidewalks, municipal buildings, packing and tool processing plants, distilleries, wineries, dairies, breweries and soft drink bottling plants. DRESS & SEAL WB treated surfaces are compatible with most paints and tile adhesives seven days after application. Complies with ASTM-C 309, Type 1, 1D.

#### COVERAGE AND PACKAGING

DRESS & SEAL WB available in 5 and 55 gallon containers.

#### Coverage Rates

- First coat, curing: 200 sq. ft/gallon to 300 sq. ft/gallon
- Second coat, sealing: 400 sq. ft/gallon to 600 sq. ft/gallon