

LATICRETE[®] 4237

Latex Thin-Set Mortar Additive

PRODUCT NAME

LATICRETE[®] 4237 Latex Thin-Set Mortar Additive

PRODUCT DESCRIPTION

LATICRETE 4237 Latex Thin-Set Mortar Additive is a specifically designed latex additive for use with Portland cement to make slurry bond coats for mortar beds and with thin set mortars to give improved performance and longer open time.

Uses-Used for installation of all types of ceramic tile, brick and natural stone.

ADVANTAGES

- Superior bond strength - 250% greater than ANSI A118.4 (American National Standard Specification for Latex Portland Cement Mortar).
- Flexible and shock resistant, rated for extra heavy traffic conditions.
- Weather and frost resistant for interior and exterior use in all types of climates.
- Safe, economical and easy to use; non-hazardous, non-flammable.

SUITABLE SUBSTRATES

- Concrete
- Brick Masonry
- Concrete Masonry
- Cement Mortar Beds
- Gypsum Wallboard (Interior Only)
- Cement Terrazzo
- Cement Plaster
- Cement Backer Board
- Ceramic Tile and Stone

PACKAGING AND COVERAGE

- 5 US gallon (19 liter) Pail, 36 per pallet
- 55-65 ft² (5.1-6m²) per 1 US gallon (3.8 l) using 1/4" x 1/4" (6 x 6 mm) square notch trowel
- 40-50 ft² (3.7-4.6m²) per 1 US gallon (3.8 l) using 1/4" x 3/8" (6 x 9 mm) square notch trowel

INSTALLATION

Surface Preparation

All surfaces should be between 40°F (4°C) and 90°F (32°C) and structurally sound and clean. Installation may be made on a damp surface.

MASONRY

