



4225 W. Ogden Ave. • Chicago, IL 60623 • Phone: (773) 522-1900

# DOW CORNING 790 SILICONE SEALANT

## DESCRIPTION

Dow 790 is a single component, ultra low modulus moisture curing silicone particularly effective for sealing expansion and control joints, precast concrete panel joints and stone pavers. 790 offers unprimed adhesion to concrete, masonry, limestone, glass, granite, and more porous surfaces. (Some non-porous surfaces, primarily aluminum, require priming. Check compatibility prior to use)

## APPLICATION

Surface must be clean, sound, dry, and free of contaminants. If required, prime surfaces prior to the insertion of backing materials. Apply Dow 790 in a continuous operation using positive pressure. Tool with concave profiled instrument.

## SPECIFICATIONS

- ASTM C-920 Type S, Grade NS, Class 25
- Fed. Spec TT-S-001543A  
TT-S-00230C
- Fire Test of Bldg. Construction & Material UL-263 (ASTM E-119)

## COLORS

Black	Blue Spruce
Precast White	Rustic Brick
Gray	Sandstone
Natural Stone	Charcoal
Bronze	Dusty Rose
Adobe Tan	

## PACKAGING

10.3 oz. Cartridges  
 20 oz. E-Z Pack Sausages  
 2 gallon Bulk Pail  
 4.5 gallon Bulk Pail

WATERPROOFING

