



4225 W. Ogden Ave. • Chicago, IL 60623 • Phone: (773) 522-1900

## VOCOMP®-20

### WATER-BASE ACRYLIC CURING AND SEALING COMPOUND

#### DESCRIPTION

SEALTIGHT VOCOMP-20 Water-Base Acrylic Curing and Sealing Compound is formulated of special acrylic copolymers in a true water-base carrier. It is a ready-to-use curing and sealing compound. Once applied, VOCOMP-20 provides an impermeable seal for efficient moisture retention. VOCOMP-20 dries clear to provide a transparent sheen finish. VOCOMP-20 resists yellowing due to ultraviolet degradation and provides a durable, long-lasting finish that offers improved resistance to chemicals, petroleum and abrasives.

#### USES

VOCOMP-20 Water-Base Acrylic Curing and Sealing Compound may be quickly and easily spray-applied to simultaneously cure and/or seal new interior and exterior, vertical and horizontal concrete surfaces. It is ideal for application on commercial and industrial floors, sidewalks, basement and garage floors, multi-level parking decks, patios, driveways and parking areas.

#### SPECIFICATIONS

- ASTM C 309, Type 1, Class B
- AASHTO M 148, Type 1, Class B

#### PACKAGING & COVERAGE

Available in 5 & 55 gallon drums  
Coverage: Approximately 300 sq. ft per gal.

## LIN-SEAL®

### ANTI-SPALL PENETRATING SEALER

Reduces spalling and scaling caused by deicing salts, water and other destructive materials.

SEALTIGHT LIN-SEAL Penetrating Concrete Sealer is a liquid formulation of boiled linseed oil in mineral spirits developed to protect and prolong the life of concrete surfaces against over exposure to deicing salt, water and other destructive materials.

#### Uses

SEALTIGHT LIN-SEAL Penetrating Concrete Sealer is ideal for application on Portland Cement Concrete bridge decks, parking garage decks and ramps, or any concrete surface which allows the concrete to absorb water, salts or other destructive materials.

#### Application

**SURFACE PREPARATION:** Surfaces to be sealed must be clean and dry.

**APPLICATION:** New concrete should be cured a minimum of 28 days before application.

Apply with a hand or power sprayer.

#### Specifications

AASHTO M 233

#### PACKAGING & COVERAGE

Available in 5 & 55 gallon drums  
Coverage: **2 coats**—1st coat: 300 sq. ft/ gal.  
2nd coat 600 sq. ft/gal