



4225 W. Ogden Ave. • Chicago, IL 60623 • Phone: (773) 522-1900

ALUMINUM AND FIBERGLASS LADDERS

AE2000 SERIES Aluminum Extension Ladder

Extra heavy duty I-beam side rails. Designed for 300 lb. workload set at the proper working angle.



QuickLatch Quicklatch equipped runglock provides easier method of securing fly and base sections when extended. One finger operation



Swivel Safety Shoes Extra heavy duty cast aluminum shoes with thick rubber tread. Full swivel safety shoe can be used with tread down or in spike position.



D-Shaped or Round Rungs Tempered aluminum rungs are hydraulically double crimped to side rails and fully serrated for a slip-resistant surface. Available in both D-Rung and round rung models.

SPECIFICATIONS

Sizes	Rail Depth	Stack Height	Inside Base	Width Fly	Outside Base	Width Fly
16' - 24'	3"	5 1/4"	15 9/16"	13 1/16"	17 13/16"	15 5/16"
28' - 40'	3"	5 1/4"	15 3/8"	13 1/4"	18"	15 7/8"

D RUNG—SINGLE LADDERS

D RUNG—TWO SECTION EXTENSION LADDERS

Model	Total Length	Approx. Weight	Approx. Cubes	Model	Total Length	Max Ea. Section	Extended Length	Approx. Weight	Approx. Cubes
AE2108	8'	14	3.78	AE2216	16'	8'	13'	30	6.38
AE2110	10'	17	4.67	AE2220	20'	10'	17'	37	7.89
AE2112	12'	20	5.57	AE2224	24'	12'	21'	42	9.41
AE2114	14'	24	6.47	AE2228	28'	14'	25'	55	10.92
AE2116	16'	31	9.16	AE2232	32'	16'	29'	62	12.55
AE2120	20'	40	11.32	AE2236	36'	18'	32'	74	14.08
				AE2240	40'	20'	35'	82'	15.61

FE0600 SERIES Fiberglass Extension Ladder

A heavy duty extension ladder designed for a 225 lb. workload when set at the proper working angle. The ideal non-conductive ladder for painters, electricians and general industrial use. Full channel fiberglass side rails.



D-Shaped Rungs—Big 1-5/8" tempered aluminum rungs are hydraulically double crimped to side rails and serrated for a slip-resistant surface. Greater standing area than round rungs.



Swivel Safety Shoes—Heavy duty plated steel shoes with thick rubber tread. Shoe can be used with tread down or in spike position.



QuickLatch—QuickLatch equipped runglock provides easier method of securing fly and base sections when extended. One finger operation.



Mar-Resistant Rail End Caps—Impact resistant caps on all rail ends for protection, longer life and durability. The caps also protect work surfaces from marring.



Rope and Pulley—All aluminum 1 1/4" pulley standard on all sizes. Comes with a 5/16" non-rotting polypropylene rope for all weather performance.

D RUNG—TWO SECTION EXTENSION LADDERS

SPECIFICATIONS

Model	Total Length	Length Each Section	Max. Extended Length	Approx. Weight	Approx. Cubes	Sizes	Rail Depth	Stack Height	Inside Base	Width Fly	Outside Base	Width Fly
FE0616	16'	8'	13'	28	6.4	16'-28'	3 1/4"	5 3/4"	15 1/16"	12 1/16"	17 7/16"	14 7/16"
FE0620	20'	10'	17'	34	7.9							
FE0624	24'	12'	21'	46	9.5							
FE0628	28'	14'	25'	53	11.0							

COMZAFLOO-3