



4225 W. Ogden Ave. • Chicago, IL 60623 • Phone: (773) 522-1900

POLYETHYLENE CONSTRUCTION FILM

SPECIFICATION

Water Vapor Transmission: <.06 perms
 Gauge: +7% average specified thickness
 Density: .910 - .965

Mil	Size	Roll Weight
4.0	8' x 100'	15.3 lbs.
4.0	10' x 100'	19.1 lbs.
4.0	12' x 100'	23.0 lbs.
4.0	16' x 100'	30.6 lbs.
4.0	20' x 100'	38.3 lbs.
4.0	24' x 100'	45.9 lbs.
4.0	28' x 100'	53.6 lbs.
4.0	40' x 100'	76.5 lbs.
8.0	20' x 100'	76.6 lbs.



Mil	Size	Roll Weight
6.0	8' x 100'	23.0 lbs.
6.0	10' x 100'	28.7 lbs.
6.0	12' x 100'	34.5 lbs.
6.0	16' x 100'	46.0 lbs.
6.0	20' x 100'	57.4 lbs.
6.0	24' x 100'	68.9 lbs.
6.0	28' x 100'	80.4 lbs.
6.0	40' x 100'	114.8 lbs.
10.0	20' x 100'	95.7 lbs.

Available immediately in Clear - White & Black available on special order



EXPAND-O-FLASH

Roof Expansion Joint Cover


Expand-O-Flash expansion joint covers are flexible, weatherproof, exterior covers for expansion joint openings and are an effective, flexible closure for a wide variety of standard and special applications. Each Expand-O-Flash cover is a combination of a flexible rubber membrane, supported by a closed cell foam to form flexible bellows, with two metal flanges, adhesively and mechanically combined to the bellows by a patented bifurcation process.

Flexible rubber membranes are available in white or black 60 mil EPDM, and black 60 mil Neoprene. Black EPDM is recommended for budget installations. White is used where color is important.

Metal flanges are available in galvanized steel (26 ga.), mill finish aluminum (0.032"), stainless steel (0.018") and copper (16 oz.). Galvanized is recommended for budget installations. Aluminum is recommended for areas where longer exposure to severe elements is required. Stainless steel is effective on manufacturing facilities where corrosion could effect longevity of the metal. Copper is used to match other copper metal work.

Selection Chart for Standard Sizes

Type N (Neoprene) or Type E (EPDM)



Joint Opening or Span			Style EJ		
Roof-to-Wall	Roof-to-Roof	Bellows Width	Foam Thickness	Style	Length
1" to 2"	1 1/2" to 2 1/2"	4"	3/8"	EJ-4	10 ft./50 ft.
2" to 3"	2 1/2" to 3 1/2"	6"	1/2"	EJ-6	10 ft./50 ft.
3" to 4"	3 1/2" to 5"	8"	1/2"	EJ-8	10 ft./50 ft.
4" to 5"	5" to 6 1/2"	10"	5/8"	EJ-10	10 ft.
5" to 6"	6 1/2" to 8"	12"	3/4"	EJ-12	10ft.

COMZPTMOO-S