



4225 W. Ogden Ave. • Chicago, IL 60623 • Phone: (773) 522-1900

F.H. Leinweber Company, Inc. Elastex

BASIC USE

ELASTEX is a floor underlayment product consisting of a powder and liquid latex additive. ELASTEX is used to smooth and level interior concrete and wood surfaces prior to the installation of finished floor covering such as vinyl-composition tile, all hard tiles, ceramic tile, quarry tile, marble, granite, wood parquet, carpet, glue down carpet and carpet squares, etc. Use ELASTEX outdoors to smooth rough concrete or masonry surfaces, ideal for stairs, risers, and columns and may be applied by brush to create a non-slip surface. ELASTEX is ideal when used to ENCAPSULATE existing vinyl asbestos tile (or cut-back adhesive), which is the preferred method over the alternate method of complete abatement

COVERAGE
1 Large Unit covers 200 sq. ft. @ 1/8"
AVAILABILITY
Large Unit — 5– 40 lb. Bags & 1– 5 gal. Liquid

2011-10-10

Jif-Set

BASIC USE

JIF-SET is a two component, powder & liquid latex, floor patch/underlayment used for patching and leveling interior subfloors prior to finished floor covering. May be used over any sound concrete or wood subfloor, or for repairing cracks or holes in interior walls, and should be installed after drywall and taping. When mixed with LEINWEBER'S LATEX/SILICONE LIQUID, JIF-SET is self-bonding.

COVERAGE
25 lb. Bag w/ 3/4 gal. Liquid yields 27 sq. ft. @ 1/8"
AVAILABILITY
25 lb. Bags

Vinyl Crete

Cementitious Topping / Floor Underlayment

DESCRIPTION & USE

VINYL-CRETE is a two component (powder & latex/vinyl additive) floor underlayment material used for leveling, smoothing, and patching both interior and exterior surfaces prior to the installation of finished floor covering. VINYL-CRETE may also be left as a wearing surface or painted. Use VINYL-CRETE over concrete, wood, tiles, metal. Excellent for covering properly bonded vinyl asbestos tile and cutback adhesive and for filling in voids of embossed sheet goods. VINYL-CRETE is formulated for use under virtually any floor tile, carpet, or finish.

COVERAGE
Large Unit Covers 200 sq. ft. @ 1/8"
AVAILABILITY
Large Unit — 5– 40 lb. Bags 1– 5 gal. Liquid