



4225 W. Ogden Ave. • Chicago, IL 60623 • Phone: (773) 522-1900

HydroPlug

Fast Setting Hydraulic Cement

**STOP ACTIVE WATER LEAKS | FILLING HOLES
ANCHORING EQUIPMENT AND MACHINERY**

In one application

2011-10-17

DESCRIPTION

Hydro-Plug is a special blend of cement, aggregates, fast set powder and modifiers. Hydro-Plug offers the ultimate in workability. Designed to be gloved hand or trowel applied in one or more applications. Use to quickly patch & repair active leaks, holes or anchoring equipment and machinery.

APPLICATION FEATURES

PERFORMANCE BENEFITS

- Easy to mix and finish
- Long lasting formula
- Sets in approximately 2 to 5 minutes at 70°F
- Excellent compressive strengths
- Extra rich for smooth troweling
- Highly versatile
- Mix with water or Latex Liquid

FOR BEST RESULTS

Apply to clean, sound and stable substrates only.
 Do not apply below 40°F
 Cracks or holes must be opened a minimum of 3/4" wide
 Wait for leaking water to stop or reach its lowest ebb
 Place mixed material with trowel edge onto surface and hold in place until firmly set
 Mix with Latex Liquid to increase bond strengths
 Mix with clean luke warm water for faster set time
 Always add cement powder into water or Latex Liquid.
 A putty like consistency is recommended.

PACKAGING AND MIXING
 Mix with water or Latex Liquid for better bonding
3 lb. Unit | 10 lb. Unit | 48 lb. Economy Unit

SuperSmooth Embosser

Polymer Modified Fine Finishing Mortar

Super Fine Finishing - Trowels Like Butter

SuperSmooth Embosser is a 1 component, polymer modified, high performance resurfacing mortar. **SuperSmooth Embosser** is simply mixed with water and applied over concrete, wood, ceramic, or linoleum from featheredge to 1/2" thick in one application. Apply horizontal, vertical, or overhead. Product sets in 20 to 45 minutes and ready for light traffic in 1 to 4 hours at 70°F.

Product Description

SuperSmooth Embosser is a special blend of cements, aggregates and exclusive modifiers. Designed for general-purpose and high performance repair or resurfacing applications.

Recommended Placement Guidelines

Up to 2 gallons of water is required to mix 35 lb of product. Always add and mix product into water. Rub or scratch mixed material onto surface just prior to application. Apply to clean and sound substrates only.

PACKAGING AND YIELD
SuperSmooth Embosser is packaged in 15 lb. pails or 35 lb. Heavy-duty polyethylene-line bags. A 35 lb. bag will cover approximately 35 sq. ft. at 1/8".