

LIGHT DUTY CONCRETE CLEANER

General purpose construction stain remover

DESCRIPTION AND USE

Sure Klean® Light Duty Concrete Cleaner removes common construction and atmospheric staining from smooth architectural and engineered concrete. This general-purpose, nonetching acidic cleaner removes rust, mud, oil, atmospheric dirt, mortar smears and other stains without altering the surface texture. Light Duty Concrete Cleaner adds depth to colors, brightens white matrices and exposed aggregate.

ADVANTAGES

- Improves color uniformity and enhances appearance.
- Removes common construction stains and atmospheric dirt.
- Removes localized rust and other metallic staining on unpolished limestone, travertine and marble. Always test.
- Safe for most pigmented concrete and colored mortar.
- Water rinseable

PREPARATION

Protect people, vehicles, property, metal, painted surfaces, plants and other nonmasonry materials from product. Clean masonry before installing windows, doors, finished flooring, metal fixtures, hardware, light fixtures, roofing materials and other nonmasonry items. If already installed, protect with polyethylene before application.

Surface & Air Temperatures

Do not apply when temperature is below freezing or will be overnight.

Equipment

Apply with a soft-fiber, tampico masonry washing brush or with low-pressure spray (50 psi max) equipment fitted with acid-resistant hoses and gaskets. Don't use pressure spray above 50 psi. This drives the cleaner into the surface, making rinse difficult. May cause stains. Do not atomize. Pressure rinsing equipment providing at least 400 psi at 4-6 gpm delivered through a 15-40 degree fan spray tip often produces best cleaning results.

SAFETY INFORMATION

Product contains phosphoric and gluconic acids. MSDS and Spec Data sheets should be referred to prior to use.



APPLICATION

ALWAYS TEST each type of surface and each type of stain for suitability.

Dilutions

Recommended dilutions for use on precast, monolithic and "unit" concrete surfaces:

Exposed Aggregate

Removal of retarder, efflorescence, etc.
1 part concentrate : 2 parts water

Form-Finished Concrete

Rough-texture
1 part concentrate : 2 parts water
Standard finish
1 part concentrate : 3 parts water

Cast Simulated Stone

1 part concentrate : 3 parts water

Concrete Block, Slump Brick

1 part concentrate : 3 parts water

Architectural Smooth-Finished Concrete

1 part concentrate : 6 parts water

APPLICATION INSTRUCTIONS

1. Always prewet surface with fresh water
2. Apply Light Duty Concrete Cleaner directly to surface with recommended masonry brush or low-pressure spray
3. Let cleaner stay on the surface for 3-5 minutes or until stains are gone
4. Reapply cleaner and rinse thoroughly with fresh water to get

COVERAGE & PACKAGING

Vol. Calculations: 50 sq.ft/gal: Porous textured surface
150 sq.ft/gal: Dense smooth surface

Substrate	Type	Use?	Coverage
Architectural Concrete Block	Smooth	yes	300-400 sq. ft.
	Split-Faced	yes	
	Burnished	yes	
	Ribbed	yes	
Concrete	Brick	yes	300-600 sq. ft.
	Tile	yes	
	Precast Panels	yes	
	Pavers	yes	
	Cast-in-place	yes	
Granite	Polished	yes	300-500 sq. ft.
	Unpolished	yes	300-500 sq. ft.
Sandstone	Unpolished	yes	300-400 sq. ft.
Slate	Unpolished	yes	300-500 sq. ft.

Available in 1 & 5 gallon containers