

800 STAIN REMOVER

Metallic stain remover for brick

DESCRIPTION AND USE

Sure Klean® 800 Stain Remover is a specialty masonry cleaning product that effectively removes green vanadium stains commonly found in buff or white brick. 800 Stain Remover also removes straw stains, acid burns and other metallic discolorations from most masonry surfaces.

ADVANTAGES

- Removes tough metallic stains quickly and easily.
- Recommended for surfaces containing colored mortar.
- Water rinsable

Limitations

- Acidic contents and fumes may damage nonmasonry and acid-sensitive surfaces.

PREPARATION

800 Stain Remover is corrosive, etches glass and architectural aluminum and is harmful to wood, painted surfaces and foliage. Beware of wind drift. Fumes will also cause damage.

Clean masonry before installing windows, doors, finished flooring, metal fixtures, hardware, light fixtures, roofing materials and other nonmasonry items. If already installed, protect with polyethylene. Sure Klean Strippable Masking is appropriate for use with this product to protect windows. Maintain enough ventilation to avoid buildup of potentially damaging fumes. All caulking and sealant materials should be in place and thoroughly cured before cleaning.

Avoid exposing building occupants to fumes. On occupied buildings, cover all windows, air intakes and exterior air conditioning vents. Shut down air handling equipment during cleaning and until surfaces are thoroughly dry. Maintain ventilation until surfaces are thoroughly dry.

Before removing metallic stains (vanadium), the masonry should be thoroughly dry to reduce recurrence of stains after cleaning.

Surface and air temperature

Cleaning when temperatures are below freezing or will be overnight may harm masonry.

Equipment

Apply with low-pressure spray (50 psi max) or densely-packed, soft-fibered masonry washing brush. Pressure-water rinsing equipment with a fan-type spray tip of 15° providing at least 400-800 psi and a flow rate of 4-6 gallons per minute is best.

SAFETY INFORMATION

MSDS and Spec Data sheets should be referred to prior to use.

APPLICATION

ALWAYS TEST each type of masonry and each type of stain for suitability, dilution and results before overall application.

Dilutions

Use 800 Stain Remover in concentrate for most applications. Testing indicates if 800 Stain Remover may be diluted with equal parts water. Always pour COLD water into empty bucket first, then carefully add product. NEVER USE HOT WATER. Handle in polypropylene buckets only.

Application Instructions

EXTERIOR SURFACES

1. Prewet the masonry surface with clean water.
2. Apply Sure Klean 800 Stain Remover directly to the masonry surface.
3. Let the cleaner stay on the surface for 3-5 minutes or until stains are gone. **NOTE:** Don't let the cleaner dry into the surface.
4. Reapply cleaner and rinse with fresh water. Thorough rinsing gets all residues off the surface.

INTERIOR SURFACES

Test and follow cleaning procedure for exterior surfaces. Rinse thoroughly with fresh water. If conditions do not allow enough water for complete rinsing, use a neutralizing rinse.

COVERAGE & PACKAGING

Substrate	Type	Use?	Coverage
Fired Clay	Brick	yes	100-200 sq. ft.
	Tile	yes	
	Terra Cotta Pavers	yes	
Granite	Polished	no	N/A
	Unpolished	yes	100-200 sq. ft.
Sandstone	Unpolished	yes	100-200 sq. ft.
Slate	Unpolished	yes	100-200 sq. ft.

Available in 1 & 5 gallon containers



2011-10-10