

# FAST ACTING STRIPPER

## Multi-layer paint remover

### DESCRIPTION AND USE

Sure Klean® Fast Acting Stripper is a thixotropic stripping compound designed for removing coatings and epoxies from concrete, masonry, wood and metal surfaces. It also removes oil, grease, and waxes from concrete decks, tile and terrazo floors. Fast Acting Stripper is formulated specifically for removal of high strength paints and coatings such as epoxies, polyurethanes, and floor enamels. Additionally, Fast Acting Stripper dissolves most spray paints, marking pens, lacquers and other graffiti. Fast Acting Stripper immediately emulsifies in water and may be rinsed with cold water, hot water, or steam.

### ADVANTAGES

- Effectively removes yellowed sealers and wax build-up as well as a variety of paint coatings and graffiti.
- Specially formulated for removing the toughest coatings - effectively removes epoxy, polyurethanes, and other high strength coatings.
- Excellent for stripping oil, grease and built-up coatings from concrete decks.
- No surface neutralization required.
- Rinses with cold or hot water.
- Thixotropic consistency permits safer application with less spillage.

### LIMITATIONS

- Not recommended for wood furniture or other finely finished wood surfaces.
- Not suitable for spray applications.

### PREPARATION

Protect people, vehicles, property, glass, solvent sensitive materials, roofing material, plants and all surfaces not set for stripping from product.

Prepare surface by scraping or pressure rinsing to remove all peeling and/or loose coatings. Let the surface dry thoroughly before applying stripper.

### Surface & Air Temperatures

For maximum effectiveness, surface and air temperatures should be above 40°F and below 85°F.

### Equipment

Apply using a solvent-resistant brush or roller. Pressure water rinsing equipment should be 400-600 psi.

### SAFETY INFORMATION

Product contains methylene chloride, amine, xylene alcohol, and methyl alcohol. MSDS and Spec Data sheets should be referred to prior to use.

### APPLICATION

**ALWAYS TEST** (minimum 4 ft. x 4 ft. area) for suitability and results before overall application. Don't let stripper dry on the surface. If tests indicate long dwell times, reapply to keep the previously applied material wet.

**Do not dilute or alter product in any way.**

### Exterior Application Instructions

1. Apply a thick coating to dry surface.
2. Let stripper dwell 15-30 minutes or until coating "lifts" or shows signs of dissolving. Periodic agitation with a stiff bristle brush improves penetration. Some coatings will need multiple applications/increased dwell time.
3. Remove stripper and residue with pressure-water rinse (400-600 psi).
4. Thoroughly clean with appropriate Sure Klean® product.

### Interior Application Instructions

1. Apply a thick coating to dry surface.
2. Let stripper dwell for 5-10 minutes or until coating "lifts" or shows signs of dissolving. Periodic agitation with a stiff bristle brush improves penetration.
3. Using a low-pressure tank sprayer, apply a mist of water to the treated surface. Water helps emulsify the old sealer and dilute the stripper so residues may be more easily picked up.
4. Using a spark-proof/explosion-proof power scrubber or buffer with an abrasive, nonmetallic scrubbing pad for floors, or stiff bristled brush for walls, scrub the surface until coatings are gone. Add more water to aid scrubbing.

**CAUTION:** Using Fast Acting Stripper with vacuum machines or power-driven scrubbers that aren't explosion/spark-proof may present a fire hazard.

### COVERAGE & PACKAGING

Substrate	Type	Use?	Coverage
Architectural Concrete Block	Smooth	yes	50-75 sq. ft. 5-7 sq. m.
	Split-faced	yes	
	Burnished	yes	
	Ribbed	yes	
Concrete	Brick	yes	50-75 sq. ft. 5-7 sq. m.
	Tile	yes	
	Precast Panels	yes	
	Pavers	yes	
Fired Clay	Cast-in-place	yes	50-75 sq. ft. 5-7 sq. m.
	Brick	yes	
	Tile	yes	
Marble, Travertine, Limestone	Terra Cotta	yes	50-75 sq. ft. 5-7 sq. m.
	Pavers	yes	
		yes	
Granite	Polished	yes	50-75 sq. ft. 5-7 sq. m.
	Unpolished	yes	
Sandstone	Unpolished	yes	50-75 sq. ft. 5-7 sq. m.
Slate	Unpolished	yes	50-75 sq. ft. 5-7 sq. m.

Available in 1 & 5 gallon containers