

ASPHALT & TAR REMOVER

Multi-purpose cleaner for masonry & concrete

DESCRIPTION AND USE

Sure Klean® Asphalt & Tar Remover is a multipurpose solvent cleaner for masonry and concrete. It is easy to apply and water rinsable. Ideal for cleaning and surface preparation, Asphalt & Tar Remover will not damage most masonry or concrete. It removes:

- Asphalt
- Tar (roofer's stain)
- Grease
- Hydraulic Oil
- Motor Oil
- Chewing Gum
- Crayon
- Lipstick

ADVANTAGES

- Removes many sealers and protective treatments such as old curing compounds, acrylic, stearate, and chlorinated rubber sealers

PREPARATION

Protect people, vehicles, property and all solvent-sensitive surfaces from contact with cleaner. Asphalt & Tar Remover may damage synthetic finishes (such as window gaskets, caulking, sealants, acrylic or polycarbonate sheeting, reflective films, and plastic), wood, roofing materials, paint, and all solvent-sensitive surfaces. If such items are to remain in place, protect before overall application.

Surface and air temperatures

Best air and masonry surface temperatures for cleaning are 40°F or above.

Equipment

Asphalt & Tar Remover can be applied with a brush or low-pressure (40 psi) spray equipment equipped with solvent-resistant hoses and gaskets. Water rinsing equipment with pressure of 400 to 800 psi at a flow rate of 4 to 6 gallons a minute is generally most effective.

Don't apply Asphalt & Tar Remover with pressure spray above 50 psi. This drives the cleaner deep into the surface, making thorough rinse difficult.

SAFETY INFORMATION

Product contains methylene chloride & xylene. MSDS and Spec Data sheets should be referred to prior to use.

APPLICATION

ALWAYS TEST each type of surface and stain for suitability and results before overall application.

Use in concentrate. DO NOT DILUTE OR ALTER.

Application Instructions

1. Apply Asphalt & Tar Remover liberally to the dry surface using low-pressure (40 psi) spray, or a brush.
2. Let the cleaner dwell for 3-4 minutes.
3. Reapply cleaner. Brush the stained area vigorously.
4. Rinse thoroughly with water to remove residue. Pressure-washing is the preferred method to minimize waste materials. Rinse from bottom to top. Keep the wall below wet and rinsed free of cleaner and residues.

ZOWIE

COVERAGE & PACKAGING

Substrate	Type	Use?	Coverage
Architectural Concrete Block	Smooth	yes	100 sq. ft.
	Split-Faced	yes	
	Burnished	yes	
	Ribbed	yes	
Concrete	Brick	yes	100 sq. ft.
	Tile	yes	
	Precast Panels	yes	
	Pavers	yes	
Fired Clay	Brick	yes	100 sq. ft.
	Tile	yes	
	Terra Cotta	yes	
	Pavers	yes	
Granite	Polished	yes	100 sq. ft.
	Unpolished	yes	100 sq. ft.
Marble Travertine Limestone	Polished	yes	100 sq. ft.
	Unpolished	yes	100 sq. ft.
Sandstone	Unpolished	yes	100 sq. ft.
Slate	Unpolished	yes	100 sq. ft.

Available in 1 and 5 gallon containers